

ROUND TUBING ELECTRIC WELD

Random 20' Lengths
Conforms to ASTM A513

Type 1: A.W.H.R. "as welded"
from hot rolled steel

Type 2: A.W.C.R. "as welded"
from cold Rolled steel



OD	Type	Wall Thickness	Weight/Foot
1/2"	2	0.049	0.236
1/2"	1	0.065	0.300
5/8"	1	0.065	0.389
3/4"	1	0.065	0.476
3/4"	1	0.083	0.591
3/4"	1	0.120	0.807
7/8"	1	0.062	0.562
1"	2	0.049	0.498
1"	2	0.065	0.650
1"	1	0.083	0.815
1"	1	0.120	1.128
1-1/8"	1	0.120	1.288
1-1/4"	1	0.065	0.825
1-1/4"	1	0.083	1.034
1-1/4"	1	0.095	1.170
1-1/4"	1	0.120	1.448
1-1/2"	1	0.065	0.996
1-1/2"	1	0.083	1.253
1-1/2"	1	0.095	1.426
1-1/2"	1	0.120	1.769
1-5/8"	1	0.095	1.550
1-3/4"	1	0.095	1.680
1-3/4"	1	0.125	2.089
2"	1	0.083	1.700
2"	1	0.109	2.201
2"	1	0.120	2.400
2"	1	0.134	2.670
2-3/8"	1	0.120	2.880
2-3/8"	A500 GRB	0.134	3.207
2-1/2"	1	0.083	2.143
2-1/2"	1	0.120	3.050
2-7/8"	1	0.120	3.531
3"	1	0.065	2.037
3"	1	0.109	3.365
3"	1	0.120	3.694
3"	1	0.134	4.102
3"	1	0.188	5.646
3"	A500 GRB	0.250	7.343
4"	1	0.120	4.972
5"	1	0.083	3.946
5"	1	0.120	6.250
5"	1	0.250	12.680
5"	A500 GRB	0.375	18.520
6"	1	0.083	4.746
6"	1	0.120	7.530
8"	1	0.083	6.348
8"	1	0.120	10.510
8"	1	0.188	15.690
10"	1	0.120	13.180