



COLD FINISHED ROUNDS - 1018

ASTM A108 / 1018

Stock Length 12' & 20'



Size Inches	Weight / Ft Lbs	12'	20'
1/8042	0.50	
3/16094	1.12	
1/4167	2.00	
5/16260	3.12	
3/8376	4.51 . .	7.51
7/16511	6.13	
1/2668	8.02	
9/16845	10.14	
5/8	1.04	12.48 . .	20.81
11/16	1.26	15.12	
3/4	1.50	18.00 . .	30.00
13/16	1.76	21.12	
7/8	2.04	24.48	
15/16	2.35	28.20 . .	47.00
1	2.67	32.04 . .	53.40
1-1/16	3.01	36.12	
1-1/8	3.38	40.565	
1-3/16	3.77	45.24	
1-1/4	4.17	50.04 . .	83.40
1-5/16	4.60	55.20 . .	91.99
1-3/8	5.05	60.60	
1-7/16	5.52	66.24 . .	110.40
1-1/2	6.01	72.12 . .	120.20
1-9/16	6.52	78.24 . .	130.39
1-5/8	7.05	84.60	
1-11/16	7.60	91.20 . .	151.99
1-3/4	8.18	98.16 . .	163.61
1-13/16	8.77	105.24 . .	175.39
1-7/8	9.39	112.68 . .	187.80
1-15/16	10.02	120.24 . .	200.40
2	10.68	128.16 . .	213.60
2-1/16	11.36		227.20
2-1/8	12.06		241.20
2-3/16	12.78	153.36 . .	255.60
2-1/4	13.52		270.41
2-5/16	14.28		285.60
2-3/8	15.06		301.20
2-7/16	15.87		317.40
2-1/2	16.69	200.28 . .	333.79
2-5/8	18.40		367.99
2-11/16	19.29		385.80
2-3/4	20.20	242.40 . .	403.99
2-7/8	22.07	264.84 . .	441.41
2-15/16	23.04		460.80
3	24.03		480.60
3-1/8	26.08		521.59
3-1/4	28.21		564.19
3-7/16	31.59		631.70
3-1/2	32.71		654.19
3-3/4	37.55		751.00
3-7/8	40.13		802.61
3-15/16	41.44		828.79
4	42.73	512.76 . .	854.59



COLD FINISHED ROUNDS - 1018

ASTM A108 / 1018

Stock Length 12' & 20' (cont.)



Size Inches	Weight / Ft Lbs	12'	20'
4-7/16	52.58 1051.58
4-1/2	54.08 1081.60
4-3/4	60.25 1204.99
5	66.76 1335.19
6	96.13 1922.59

COLD FINISHED ROUNDS 1045

Stock Length 12' - 20' - 24' Random

Size Inches	Weight / Ft Lbs	12'	20'	24'
3/8376	4.51	7.51	
1/2668	8.02		
5/8	1.040	12.48		
3/4	1.500		30.00	
7/8	2.040	24.48		
1	2.670	32.04	53.40	
1 TGP	2.670			64.08
1-1/16	3.010		60.19	
1-1/8	3.380	40.56	67.60	
1-3/16	3.770	45.24		
1-1/4	4.200	50.40	83.40	
1-5/16	4.6		92.00	
1-3/8	5.050	60.60		
1-7/16	5.520	66.24		
1-1/2	6.010	72.12	120.20	
1-5/8	7.050	84.60		
1-3/4	8.180		163.60	
2	10.680	128.16		
2-1/16	11.360	227.21		
2-3/16	12.780		255.60	
2-1/4	13.52		270.41	
2-3/8	15.060		301.20	
2-7/16	15.870		317.40	
2-1/2	16.690	200.30	333.84	
2-3/4	20.2		403.99	
3	24.030		480.60	
3-7/16	31.590		631.70	
3-1/2	32.71		654.20	
3-3/4	37.550		751.01	
4	42.730		854.60	

COLD FINISHED ROUNDS 12L14

Stock Length 12' Random

Size Inches	Weight / Ft Lbs	12'
1/4	0.155	1.86
5/16	0.260	3.12
3/8	0.376	4.51
1/2	0.668	8.02
5/8	1.040	12.48
3/4	1.500	18.00
7/8	2.040	24.48
1	2.670	32.04



COLD FINISHED ROUNDS

12L14

Stock Length 12' Random



Size Inches	Weight / Ft Lbs	12'
1-1/16	3.096	37.15
1-1/8	3.380	40.56
1-1/4	4.200	50.04
1-3/8	5.050	60.60
1-1/2	6.010	72.12
1-3/4	8.18	98.16
2	10.68	128.16
2-1/2	16.90	200.275
3	24.03	288.36

COLD FINISHED ROUNDS 1215

Stock Length 12' Random Length

Size Inches	Weight / Ft Lbs	12'
3/8	0.376	4.51

COLD FINISHED ROUNDS

4140 / 4142 PURPLE – 12' Random Length

Size Inches	Weight / Ft Lbs	12'
1	2.670	32.04
2	10.680	128.16



**STRESS RELIEVED
ROUNDS 1144**

Cold Finish, AST A311
12' Random Length



Size Inches	Weight / Ft. Lbs.	12'
1/4	0.167 . . .	2.00
5/16	0.260 . . .	3.13
3/8	0.376 . . .	4.51
7/16	0.511 . . .	6.13
1/2	0.668 . . .	8.02
9/16	0.845 . . .	10.14
5/8	1.040 . . .	12.48
11/16	1.260 . . .	15.12
3/4	1.500 . . .	18.00
13/16	1.760 . . .	21.12
7/8	2.040 . . .	24.48
15/16	2.350 . . .	28.20
1	2.670 . . .	32.04
1-1/16	3.010 . . .	36.12
1-1/8	3.380 . . .	40.56
1-3/16	3.770 . . .	45.24
1-1/4	4.170 . . .	50.04
1-5/16	4.600 . . .	55.20
1-3/8	5.050 . . .	60.60
1-7/16	5.520 . . .	66.24
1-1/2	6.010 . . .	72.12
1-9/16	6.520 . . .	78.24
1-5/8	7.050 . . .	84.60
1-11/16	7.600 . . .	91.20
1-3/4	8.180 . . .	98.16
1-7/8	9.390 . . .	112.68
1-15/16	10.020 . . .	120.24
2	10.680 . . .	128.16
2-1/16	11.360 . . .	136.32
2-1/8	12.060 . . .	144.72
2-3/16	12.780 . . .	153.36
2-1/4	13.520 . . .	162.24
2-3/8	15.060 . . .	180.71
2-7/16	15.870 . . .	190.44
2-1/2	16.690 . . .	200.28
2-5/8	18.400 . . .	220.80
2-11/16	19.310 . . .	231.70
2-3/4	20.190 . . .	242.40
2-7/8	22.070 . . .	264.84
2-15/16	23.040 . . .	276.48
3	24.030 . . .	288.36
3-1/4	28.210 . . .	338.52
3-7/16	31.590 . . .	379.02
3-1/2	32.710 . . .	392.52
3-3/4	37.550 . . .	450.60
4	42.730 . . .	512.76
4-1/2	54.130 . . .	649.50